

Model **1805 - Snowflake 1**

Dimensions

Seat Height	15.0	Depth	15.0
Seat Width	13.0	Width	15.25
Overall Height	24.0		



COM Yardage

Based on pattern repeats less than 5 in. x 5 in.

Unit	0.83
Seat Yardage	0.33
Back Yardage	0.5
Stacking	4 high on floor

Options:

Wall saving	No
Connected	No
Tablet	No
Arms	No
CAL 133	Yes
Dolly	No

Frame construction

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal.

Seat

The upholstered seat foundation is based on a 3/8 in. thick, 7 ply laminated contoured plywood core platform with upholstery covers form fitted and stapled over 1 inch thick hi-resiliency polyurethane foam.

Back

The upholstered back foundation is based on a 3/8 in. thick, 6 ply laminated contoured plywood core platform with upholstery covers form fitted and stapled over 1 inch thick hi-resiliency polyurethane slab cut foam.

Foam

Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Glides

Frame feet are finished with durable injection molded plastic glides.

Load Test

Exceeds BIFMA Seating Durability Test to 250 lbs