



Model **2201CHD - Heavy Duty 2000 Series, Sled Base, Single Seater**
1 Piece Seat and Back

Dimensions

Seat Height	18.00	Depth	26.50
Seat Width	22.00	Width	25.00
Overall Height	35.00	Arm Height	26.00

COM Yardage Based on pattern repeats less than 5 in. x 5 in.
 Unit 1.75

Options:

Wall saving	No
Connected	Yes
Cal 133	Yes

Frame Construction Constructed of high carbon content cold rolled seam welded flash controlled steel tube free of crimping on all bends, Offered in 1 1/2" 16GA O.D. Tube which is filled with steel shot. All connections are metal to metal.

Seat and Back Upholstered material is applied to hi-resiliency molded foam. A reinforced fiberglass armature is encapsulated inside the foam. This assembly provides strength and stability for the molded foam. Seat and back covers are zipper locked and removable in the field. The one piece seat and back are bolted to the frame with four 1/4-20 tamperproof fasteners.

Foam Molded foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 3.0 to 3.2 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117).

Glides Frame feet are finished with non-removable 1 1/8" steel levellers with a 1/4- 20 steel stem.

Load Test Exceeds BIFMA Seating Durability Test to 500 lbs