

**Model** 2201C - 2000 Series, 4-Point, Single Seat with Arms  
1 Piece Seat and Back

**Dimensions**

Seat Height	18.00	Depth	26.50
Seat Width	22.00	Width	25.00
Overall Height	35.00	Arm Height	26.00



**COM Yardage** Based on pattern repeats less than 5 in. x 5 in.  
**Unit** 1.75

**Options:**

Wall saving	No
Connected	Yes
CAL 133	Yes
Arm Styles	Black polyurethane arm pads

**Frame Construction** Constructed of high carbon content cold rolled seam welded flash controlled steel tube free of crimping on all bends, Offered in 1 1/2" 16GA O.D. Tube. Seat support is provided by a 1/4" thick steel plate welded to the frame. All connections are metal to metal.

**Seat and Back** Upholstered material is applied to hi-resiliency molded foam. A reinforced fiberglass armature is encapsulated inside the foam. This assembly provides strength and stability for the molded foam. Seat and back covers are zipper locked and removable in the field.

**Foam** Molded foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 3.0 to 3.2 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

**Flame retardancy** Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

**Arms** Optional molded self-skinned urethane arm caps available. The arm cap is molded over a 1/8 in. thick steel flat plate which is attached to the seat frame using metal-to-metal connections using 1/4-20 bolts. Polyurethane arm caps are field replaceable.

**Glides** Frame feet are finished with durable injection molded plastic glides.

**Load Test** Exceeds BIFMA Seating Durability Test to 500 lbs