

**Model** 6301M - Mission, Medium Back, Single Seat with Arms

**Dimensions**

Seat Height	18	Depth	25
Seat Width	21	Width	25.25
Overall Height	33.75	Arm Height	25

**COM Yardage** Based on pattern repeats less than 5 in. x 5 in.

Unit	1.75
Seat Yardage	0.75
Back Yardage	1

**Options:**

Wall saving	No
Connected	Yes
Cal 133	Yes
Arm Styles	Wood or Black polyurethane - flat or rounded profile
Leg Guard	Yes



**Frame construction** All end and connecting wood frames are assembled from the highest quality European Beech. The wood frame is mechanically fastened to a welded substructure. The substructure uses a combination of 10 and 11 gauge brake-formed sheet metal parts to create the foundation to which suspension, support components and frame subassemblies are attached to form the completed chair frame.

**Seat** The upholstered seat pan is made with 100% recycled plastic with upholstery covers form fitted and stapled over 3 inch thick hi-resiliency polyurethane molded foam.

**Back** The upholstered back is based on a 3/4 in. thick, 7 ply laminated contoured plywood core platform with velcro-removable upholstery covers form fitted over 4 inch thick hi-resiliency polyurethane molded foam.

**Foam** Molded foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 3.0 to 3.2 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

**Flame retardancy** Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

**Arms** A molded self-skinned urethane arm is available in a flat (PF) or rounded (PR) shape. The arm is molded over a 1/8 in. thick steel flat plate which is attached to the seat frame using metal-to-metal connections.

**Glides** Frame feet are finished with durable injection molded plastic glides.

**Load Test** Exceeds BIFMA Seating Durability Test to 500 lbs