

Model: Factory

Options:
Casters



FCT The base is constructed by welding four 2" x 2" 14ga. steel tubes together in a square shape pattern. Two inserts are welded to the bottom of each leg and tapped for an adjustable leveler. Welds on the base are polished on both the front and back face of the joint with all tube seams aligned on the inside of the base. The bottom stretcher is made from 2" x 2" 14ga. tube and are mechanically fastened between the two Factory bases during install. Second bottom stretcher may be specified at an upcharge, in which case stretchers are pushed out to each side to make footrests for the table. Ships knocked down.

Tops
Laminate Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core with a 2" built-up edge, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per cu. ft.

Edges
SE See Laminate above
2MM 2MM edges are made from pellet material that is melted and extruded through a die-head profile. The edge is adhered to the core material and trimmed into place with a state of the art edge bander, resulting in a virtually pick proof edge. 2MM BIO EDGE has a bio-based content of 88% that is made from rapidly renewable corn. The portion of the corn used is a waste byproduct and therefore not taken from food stock. Contains no hazardous chemicals and emits no toxic VOC's and is recyclable. 2mm Bio edge has the impact durability of PVC with a profile similar to self edge. Available in 38 solid colors. 2MM PVC EDGE is a polyvinyl chloride extruded plastic edge with a profile similar to self edge. Available in wood grain to match 9 standard stains.

Casters (Optional) NSF certified, industrial grade grey casters are pressed steel, bright zinc plated, and with a double ball bearing swivel head. Polypropylene wheel body with an injected rubber tread and plain bearing. 4" in diameter (5" overall height), 1-1/4" tread width. With a dynamic load capacity of 250 lbs per wheel, the wheels are total lock, non-marking, quiet, require minimal maintenance, are easy to clean, and provide easy maneuverability.