



Model: Sidekick

Standard Options:

Custom Heights

Custom Sizes



Base

Column uprights and feet are constructed of 14 gauge seam-welded cold rolled steel square or round tube with the column being 2.0" and the base steel disc cover being 16 gauge ranging in diameter to match the top size. An inner 3/8" thick counter weight is inserted under the whole circumference of the steel disc cover plate for both support and to provide weight to give stability to the top. A 1/4" thick 9" x 9" mounting plate is welded to the top of the column, then drilled and tapped to accept 8- 7/8" deep root screws. The counter weight is mechanically fastened to the column and is finished with 1/2"-18 screw-threaded durable zinc lellers.

Tops

Laminate
Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in. The top edge is routed to accept our PVC molding (Flat, Bullnose or Rigid) to match or accent the top, or self edge and further bonded in place with a water based white glue.

Veneer

Veneer tables are offered constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/32" hand laid up flat cut veneer on top and bottom for a sandwich top thickness of 1 1/16". Veneers are selected with careful attention to grain matching and symmetry. The table edge is finished with one of several hardwood edge profiles.

Edges

PVC
Edges are made from PolyCor G92B poly-vinyl choride (PVC) pellet material melted and extruded through one of several die-head profiles. The matching or accented PVC edge is both glued and fitted to the table core using a continuous tongue and groove system around the circumference of the table.

Hardwood

Spec hardwood edges are individually segmented, glued, using water based glues, and then clamped to the edges of the tables to assure 100% surface coverage of the glue both on the tabletop and the hardwood edge. After clamping to ensure a tight and permanent bond, the edges are then machined and hand-planed to match the exact thickness of the tabletop. All corners are mitered then pencil radiused before being sealed, stained and lacquered.

2MM Edge

2MM edges are made from pellet material that is melted and extruded through a die-head profile. The edge is adhered to the core material and trimmed into place with a state of the art edge bander, resulting in a virtually pick proof edge. 2MM BIO EDGE has a bio-based content of 88% that is made from rapidly renewable corn. The portion of the corn used is a waste byproduct and therefore not taken from food stock. Contains no hazardous chemicals and emits no toxic VOC's and is recyclable. 2mm Bio edge has the impact durability of PVC with a profile similar to self edge. Available in 38 solid colors. 2MM PVC EDGE is a polyvinyl chloride extruded plastic edge with a profile similar to self edge. Available in wood grain to match 9 standard stains.