

Model 1851 - Snowball 2, Four Point with Arms

Dimensions

Seat Height	18.0	Depth	21.5
Seat Width	18.0	Width	23.5
Overall Height	33.0	Arm Height	26.0



COM Yardage

Based on pattern repeats less than 5 in. x 5 in.

Unit	1
Seat Yardage	0.5
Back Yardage	0.5
Stacking	6 high on floor, 10 high with dolly

Options:

Wall saving	Yes
Connected	Yes
Tablet	Option
CAL 133	Yes
Dolly	Yes. Model 1899
DuraSpec Seat	Yes

Frame construction

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal.

Seat

The upholstered seat foundation is made with 100% recycled plastic with upholstery covers form fitted and stapled over 1 inch thick hi-resiliency polyurethane molded foam. The 100% recycled plastic platform covers the staples, making the seat easy to clean and provides for a smooth surface when stacking (stacking not available on Sled base).

Back

The upholstered back foundation is based on a 3/8 in. thick, 6 ply laminated contoured plywood core platform with upholstery covers form fitted and stapled over 1 in. thick hi-resiliency polyurethane slab cut foam on the front and 3/8 in. thick polyurethane foam on the back, maintaining comfort and a slim line profile. The fully upholstered back with integral outer cover conceals all mounting brackets and hardware.

Foam

Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Arms

The arm is constructed from molded nylon.

Glides

Frame feet are finished with durable injection molded plastic glides.

Sled Base Foot

An optional mechanically fastened die cast steel sled is available, excluding 18"W with wallsaving frame, and can be field installed. The sled foot can be painted any colour shown on our colour card.

Load Test

Exceeds BIFMA Seating Durability Test to 500 lbs