

Model	9101B - Tailor Single Seat Bench		
Dimensions			
Seat Height	18.0	Total D	20.0
Seat Width	23.0	Total W	23.0
Total H	18.0		
COM Yardage			
	Based on pattern repeats less than 5 in. x 5 in.		
Unit	1.25		
Seat Yardage	1.25		



Options:
CAL 133 Yes

Frame construction, non wall-saving The frames are made from 1" square steel tube welded to laser cut steel channels. Threaded inserts for the universal connecting kit have been welded to the underside of the frame so the unit can be reconfigured multiple times without the need to replace parts.

Seat A 0.75" thick plywood structure with elastic webbing across the center adds suspension to the part of the seat most commonly interacted with, topped with high-resiliency molded foam (see Foam). Seat upholstery is stapled into place along a disciplined edge, followed by a fabric cover across the bottom. Seats can be easily removed or replaced as needed by way of four bolts (per seat) underneath the frame.

Foam Foam is formulated to displace 25% of the existing non-renewable petroleum material with a sustainable plant based substitute without changing the physical properties, comfort, and longevity of the foam. The molded foam performs as regular based cut foam and provides a density of 4.2 PCF while the slab cut foam provides a density of 1.8 PCF.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Connecting Plate Universal steel connecting plate, which uses 5/16" bolts to attach the frames of Tailor chairs and tables.

Glides All frames are finished with durable injection molded polycarbonate glides.