

Model 1401-UB - Urban, DuraSpec Poly Seat & Upholstered Back, Four Point with Arms

Dimensions

Seat Height18.0Depth22.0Seat Width18.0Width24.0Overall Height32.5Arm Height27.0

COM Yardage

Unit 0.5 Back Yardage 0.5

Stacking 8 high with a dolly

Options:

Wall saving Yes
Connected Yes
Cal 133 Yes

Dolly Yes. Model 1499 Casters Yes. Model 1402

Frame construction Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on

all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat

support. All connections are metal to metal. Brazed welding is used on all exposed welds.

Seat The DuraSpec poly seat consists of over-molded polyurethane on an innovative shell made with 100%

recycled materials. Available in Black or Sterling Grey.

Back The back support structure is made from PP plastic with upholstery covers form fitted and fastened over 1

inch thick hi-resiliency polyurethane slab cut foam.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and

California Bulletin No. 117 (TB117-2013).

Arms The arm is constructed from glass-filled nylon.

Glides Frame feet are finished with durable injection molded plastic glides.

Load Test Exceeds BIFMA Seating Durability Test to 500 lbs

