



Model 1401-UP - Urban, Upholstered Seat & Back, Four Point with Arms

Dimensions

Seat Height	18.0	Depth	22.0
Seat Width	18.0	Width	24.0
Overall Height	32.5	Arm Height	27.0



COM Yardage

Based on pattern repeats less than 5 in. x 5 in.

Unit	1
Seat Yardage	0.5
Back Yardage	0.5
Stacking	8 high with a dolly

Options:

Wall saving	Yes
Connected	Yes
Cal 133	Yes
Dolly	Yes. Model 1499
Casters	Yes. Model 1402

Frame construction

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal. Brazed welding is used on all exposed welds.

Seat

The upholstered seat foundation is made with 100% recycled plastic with upholstery covers form fitted and stapled over 1 inch thick hi-resiliency polyurethane slab cut foam. The 100% recycled plastic platform covers the staples, making the seat tamperproof, easy to clean and provides for a smooth surface when stacking (stacking not available on Sled base).

Back

The back support structure is made from PP plastic with upholstery covers form fitted and fastened over 1 inch thick hi-resiliency polyurethane slab cut foam.

Foam

Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Arms

The arm is constructed from glass-filled nylon.

Glides

Frame feet are finished with durable injection molded plastic

Load Test

Exceeds BIFMA Seating Durability Test to 500 lbs

Optional Wood Back

The maple back is comprised of a minimum of 7 layers of plywood, pressed into a 0.5 inch thick tapered back, with an outer layer of maple veneer front and back. The back can be machined with one of the standard 3 designs or with a custom logo.

