

Model 1401-US - Urban, Upholstered Seat & Plastic Back, Four Point with Arms

Dimensions

Seat Height18.0Depth22.0Seat Width18.0Width24.0Overall Height32.5Arm Height27.0

COM Yardage Based on pattern repeats less than 5 in. x 5 in.

Unit 0.5 Seat Yardage 0.5

Stacking 8 high with a dolly

Options:

Wall saving Yes
Connected Yes
Cal 133 Yes

Dolly Yes. Model 1499

Frame construction Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on

all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat

support. All connections are metal to metal. Brazed welding is used on all exposed welds.

Seat The upholstered seat foundation is made with 100% recycled plastic with upholstery covers form fitted and

stapled over 1 inch thick hi-resiliency polyurethane slab cut foam. The 100% recycled plastic platform covers the staples, making the seat tamperproof, easy to clean and provides for a smooth surface when stacking

(stacking not available on Sled base).

Back The back is made from PP plastic and mechanically fastened to the frame.

Foam Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a

sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF

density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and

California Bulletin No. 117 (TB117-2013).

Arms The arm is constructed from glass-filled nylon.

Glides Frame feet are finished with durable injection molded plastic glides.

Load Test Exceeds BIFMA Seating Durability Test to 500 lbs

Optional Wood Back The maple back is comprised of a minimum of 7 layers of plywood, pressed into a 0.5 inch thick tapered back,

with an outer layer of maple veneer front and back. The back can be machined with one of the standard 3

designs or with a custom logo.



