



**Model** 1401 - Urban, DuraSpec Poly Seat & Plastic Back, Four Point with Arms

**Dimensions**

Seat Height	18.0	Depth	22.0
Seat Width	18.0	Width	24.0
Overall Height	32.5	Arm Height	27.0



**Options:**

Stacking	8 high with a dolly
Wall saving	Yes
Connected	Yes
CAL 133	Yes
Dolly	Yes. Model 1499
Casters	Yes. Model 1402

**Frame construction** Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal. Brazed welding is used on all exposed welds.

**Seat** The DuraSpec poly seat consists of over-molded polyurethane on an innovative shell made with 100% recycled materials.

**Back** The back is made from PP plastic and mechanically fastened to the frame.

**Flame retardancy** Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

**Arms** The arm is constructed from glass-filled nylon.

**Glides** Frame feet are finished with durable injection molded hard plastic glides.

**Sled Base Foot** An optional mechanically fastened die cast steel sled is available for 18"w models, excluding 18"w with wallsaving frame, stools or hip chairs. The sled may be ordered for factory prepared frames or to be field installed.

**Load Test** Exceeds BIFMA Seating Durability Test to 500 lbs

**Optional Wood Back** The maple back is comprised of a minimum of 7 layers of plywood, pressed into a 0.5 inch thick tapered back, with an outer layer of maple veneer front and back. The back can be machined with one of the standard 3 designs or with a custom logo.

