

Model 4002 - Crayon Chair without Arms

Dimensions

Seat Height	14.00	Depth	16.00
Seat Width	12.00	Width	14.00
Overall Height	26.00		



Seat and Back

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in. The top edge is routed to accept our PVC molding (Flat or Bullnose) to match or accent the top, and further bonded in place with a water based white glue. All our laminate, PVC edge tables pass BIFMA Air Quality Testing.

Legs

Legs are constructed of 16 gauge 1 1/4" round tube and fully welded to a seat support plate which is then fastened to the inserts on the underside of the seat with 1/4 -20 bolts.

Glide

The steel tubing is capped at the floor with compression fit injection molded polymer glides at the front and injected moulded polymer glides at the rear.

Load Test

Exceeds BIFMA Seating Durability Test to 500 lbs

Model 4001 - Crayon Stool

Dimensions

Seat Height	14.00	Depth	14.00
Seat Width	12.00	Width	14.00
Overall Height	14.00		



Seat Construction

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in. The top edge is routed to accept our PVC molding (Flat or Bullnose) to match or accent the top, and further bonded in place with a water based white glue. All our laminate, PVC edge tables pass BIFMA Air Quality Testing.

Legs

Legs are constructed of 16 gauge 1 1/4" round tube and fully welded to a seat support plate which is then fastened to the inserts on the underside of the seat with 1/4 -20 bolts.

Glide

The steel tubing is capped at the floor with compression fit injection molded polymer glides at the front and injected moulded polymer glides at the rear.

Load Test

Exceeds BIFMA Seating Durability Test to 500 lbs

Model 4004 - Crayon Freestanding Table

Dimensions

Round Tops	24, 30, 36	Table Height	22.00
Square Tops	24, 30		
Rectangle Tops	24 x 48		



Top Construction

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in. The top edge is routed to accept our PVC molding (Flat or Bullnose) to match or accent the top, and further bonded in place with a water based white glue. All our laminate, PVC edge tables pass BIFMA Air Quality Testing.

Legs

Legs are constructed of 16 gauge 1 1/4" round tube and fully welded to a seat support plate which is then fastened to the inserts on the underside of the seat with 1/4 -20 bolts.

Glides

The steel tubing is capped at the floor with compression fit injection molded polymer glides at the front and injected moulded polymer glides at the rear.