

# MATERIALS BREAKDOWN



# BASE & TOP CONSTRUCTION

### 8850

Two-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. Use tamper-resistant screws for assembly. Hardi is CAL 133 compliant as standard.

Sand Ballasting Capacity: 250 lbs of play sand. Ballast with bag inserted prior to pouring sand. Call Factory for more information.



# BASE & TOP CONSTRUCTION

### 8852

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Floor mount only. Hardi is CAL 133 compliant as standard.



# BASE & TOP CONSTRUCTION

#### 8851

Three-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. Use tamperresistant screws for assembly. Hardi is CAL 133 compliant as standard.

Sand Ballasting Capacity: 100 lbs of play sand per leg; there are two legs. Ballast with bag inserted prior to pouring sand. Call Factory for more information.



### BASE & TOP CONSTRUCTION

### 8853

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Floor and wall mount. Hardi is CAL 133 compliant as standard.



# BASE & TOP CONSTRUCTION

# 8854

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Wall mount only. Hardi is CAL 133 compliant as standard.



# STATEMENT OF LINE - SPECIFICATIONS

	8850	8851	8852	8853	8854
Total Height (in)	29	29	29	29	25.5
Total Depth (in)	42	42-48	24	24	20
Total Width (in)	42	42-48	36	36	36
Product Weight (Ibs)	38	54	47	35	34
Qty (pcs)/Volume (cu ft)	n/a	n/a	1/15.5	1/15.5	1/15.5