



HOSPITALITY CARTS Specification Sheet

MATERIALS BREAKDOWN



DIMENSIONS	(INCHES)
Width	36, 36, 42
Depth	20, 24
Height	36

BASE CONSTRUCTION

ALL MODELS

Constructed of 3/4" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core. Board is covered in either plastic laminate (plastic laminate one both sides) or laid up flat cut veneer on both sides. The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. Laid up board is then cut to fit outside dimensions of cabinet then cam and pin joined to form the cabinet. The doors are finished with high quality 120 degree hinges and are opened and closed using touch latch mechanisms.

TOP CONSTRUCTION

LAMINATE

Constructed of 3/4" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on both sides for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility.

VENEER TOPS

Veneer tables are offered constructed of 3/4" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/32" hand laid up flat cut veneer on top and bottom for a sandwich top thickness of 1 1/16". Veneers are selected with careful attention to grain matching and symmetry.

FEET CONSTRUCTION

CASTERS

Swivel casters with brake are twin-wheel and made of a durable polyamide center, polyurethane thread for reduced noise, and precision ball bearings secured with a steel plated stem.

CERTIFICATION

ANSI/BIFMA X5.9 Storage Units