



## JAZZY Specification Sheet

### MATERIALS BREAKDOWN



### CONSTRUCTION

#### FRAME

Frames are welded with 1/2" CNC bent cold rolled steel wire. Optional clear, rugged polyurethane film over the footrest protects surfaces from damage caused by abrasion, scratching, erosion, UV and minor impacts.

#### SHELL

Jazzy shells are constructed with 7/16" molded maple plywood with either two (2) veneer or two (2) laminate exposed faces.

#### GLIDES

Clear polycarbonate glides are friction fit to the frame.

### CERTIFICATIONS

ANSI/BIFMA X5.1 General-Purpose Office Chairs

### JAZZY DOLLY

#### FRAME

Constructed of welded hot rolled picked and oiled (HRPO) 11 gauge steel. Finished in black.

#### CASTERS

Jazzy shells are constructed with 7/16" molded maple plywood with either two (2) veneer or two (2) laminate exposed faces.

### STATEMENT OF LINE - SPECIFICATIONS



2141



2144



2147



2199

Seat Height (in)	18	24	29	
Total Height (in)	33.75	33.50	38.50	13
Seat Width (in)	16	16	16	
Total Width (in)	20.75	21	21	22.25
Depth (in)	21.5	21.5	21.5	34
Weight Rating (lbs)	275	275	275	
Product Weight (lbs)	16	17	19	
Qty (pcs) per carton	4/15	4/18	2/18	