

Model: Annex



Base - ANX

The Annex base is constructed by welding three $2" \times 4"$ 14ga. steel tubes together in an "X" shape pattern. The top of the base sees two $9" \times 9"$ top plates welded and used to connect the base to the table top. Two inserts are welded to the bottom of each leg and tapped for an adjustable leveler. Welds on the base are polished on both the front and back face of the joint with all tube seams aligned on the inside of the base. The base stretcher is made from $1" \times 2"$ 14ga. tube and is mechanically fastened between the two Annex bases during install.

Tops

Laminate

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core with a 2" built-up edge, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in.

Edges

SE 2MM

See Laminate above

2MM edges are made from pellet material that is melted and extruded through a die-head profile. The edge is adhered to the core material and trimmed into place with a state of the art edge bander, resulting in a virtually pick proof edge. 2MM BIO EDGE has a bio-based content of 88% that is made from rapidly renewable corn. The portion of the corn used is a waste byproduct and therefore not taken from food stock. Contains no hazardous chemicals and emits no toxic VOC's and is recyclable. 2mm Bio edge has the impact durability of PVC with a profile similar to self edge. Available in 38 solid colors. 2MM PVC EDGE is a polyvinyl chloride extruded plastic edge with a profile similar to self edge. Available in wood grain to match 9 standard stains.