Model **6101M - Dwight, Medium Back, Single Seat with Arms**

Dimensions

Seat Height	18	Depth	25
Seat Width	21	Width	25.25
Overall Height	33.75	Arm Height	25

COM Yardage	Based on pattern repeats less than 5 in. x 5 in.
Unit	1.75
Seat Yardage	0.75
Back Yardage	1

Options:

Wall saving	No
Connected	Yes
CAL 133	Yes
Arm Styles	Wood or Black polyurethane - flat or rounded profile
Leg Guard	Yes

Frame construction Constructed of high carbon content cold rolled seam welded flash controlled steel tubing. Offered in 1 7/8 in. O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal.

Seat The upholstered seat pan is made with 100% recycled plastic with upholstery covers form fitted and stapled over 3 inch thick hi-resiliency polyurethane molded foam.

Back The upholstered back is based on a 3/4 in. thick, 7 ply laminated contoured plywood core platform with velcro-removable upholstery covers form fitted over 4 inch thick hi-resiliency polyurethane molded foam.

Foam Molded foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 3.0 to 3.2 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Arms A wood or molded self-skinned urethane arm is available in a flat (PF) or rounded (PR) profile. The arm is molded over a 1/8 in. thick steel flat plate which is attached to the seat frame using metal-to-metal connections.

Glides Frame feet are finished with durable injection molded plastic glides.

Load Test Exceeds BIFMA Seating Durability Test to 500 lbs