

Model 9101M - Tailor Lounge Freestanding, Medium Back, Single Seat With Arms

Dimensions

Seat Height	18.0	Total D	29.0
Seat Width	23.0	Total W	29.5
Total H	33.0	Arm Height	24.5



COM Yardage Based on pattern repeats less than 5 in. x 5 in.

Unit	4.25
Seat Yardage	1.25
Back Yardage	1.50
Arm Yardage	1.50

Options:

Connected	See Modular in Price List
CAL 133	Yes
Arm Caps	Wood, Polyurethane

Frame construction The frames for both seating & tables are made from 1" square steel tube welded to laser cut steel channels. Threaded inserts for the universal connecting kit have been welded to the underside of the frame so the unit can be reconfigured multiple times without the need to replace parts.

Seat A 0.75" thick plywood structure with elastic webbing across the center adds suspension to the part of the seat most commonly interacted with, topped with high-resiliency molded foam (see Foam). Seat upholstery is stapled into place along a disciplined edge, followed by a fabric cover across the bottom. Seats can be easily removed or replaced as needed by way of four bolts underneath the frame.

Back CNC cut plywood panels create a structural box for the back, covered by high-resiliency molded foam (see Foam) to create comfortable upper back and lumbar support. Upholstery is pulled over a disciplined edge at the bottom of the back. The back can be easily detached from the frame as needed by way of four bolts.

Foam Foam is formulated to displace 25% of the existing non-renewable petroleum material with a sustainable plant based substitute without changing the physical properties, comfort, and longevity of the foam. The molded foam performs as regular based cut foam and provides a density of 4.2 PCF while the slab cut foam provides a density of 1.8 PCF.

Flame retardancy Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

Arms Arms are constructed of plywood with spacer blocks made from polypropylene. The blocks also provide attachment points for the optional arm cap hardware, ensuring consistent positioning and ease of arm cap installation/replacement. The arms are covered in hi-resiliency polyurethane slab cut foam followed by the upholstery which is pulled tightly to the curved profile. All arms bolt directly to the seat.

Glides All frames are finished with durable injection molded polycarbonate glides.